

“Obstacle Detecting Blind Stick Created Using Arduino”

Author: Anant Zade¹, Suraj Tidke², Pratik Bidkar³, Avinash Shinde⁴, Prathamesh Wagh⁵, Milind Rane⁶
GES Sir Dr. M. S. Gosavi Polytechnic Institute.

ABSTRACT

The Obstacle Detecting Blind Stick using Arduino aims to create an assistive tool to help visually impaired individuals navigate their surroundings more safely and independently. This smart stick uses an Arduino microcontroller integrated with ultrasonic sensors to detect obstacles within a certain range. When the stick detects an obstacle, it alerts the user through vibrating motors or audio signals, providing real-time feedback on potential hazards in their path. The ultrasonic sensors, positioned at strategic points, emit ultrasonic waves that bounce back upon hitting an object, allowing the system to calculate the distance to the obstacle and warn the user in advance. Additionally, the stick incorporates an alarm system that activates in emergency situations, helping the user gain attention if they need assistance. Compact and lightweight, this design ensures easy handling without compromising reliability. The project showcases the potential of affordable, user-friendly technology to improve mobility for visually impaired individuals. Overall, this Arduino-based obstacle-detecting stick combines modern electronic components in a practical application, offering a low-cost, customizable, and scalable solution that could benefit a large population and significantly enhance independence and safety for visually impaired users.

Introduction

Navigating safely and independently is one of the primary challenges for visually impaired individuals, especially in unfamiliar environments. Traditional mobility aids like the white cane provide tactile feedback when an object is directly encountered but often fail to alert users to obstacles in their path until they are very close. This limitation can create risky situations and restrict the mobility of visually impaired

individuals. With advancements in affordable electronics, however, there is now an opportunity to enhance these aids by adding real-time obstacle detection, helping users better navigate their surroundings with minimal effort.

The "Obstacle Detecting Blind Stick using Arduino" project is designed as an improved assistive device, capable of identifying obstacles and providing warnings to the user before physical contact. This smart stick leverages an Arduino microcontroller and ultrasonic sensors to detect objects within a predefined range. When the sensors detect an obstacle, the device sends a signal to a vibrating motor or speaker, notifying the user of an obstruction and its approximate distance. This feedback mechanism allows visually impaired users to gauge the proximity of obstacles without physical contact, thus enhancing their safety and mobility.

Ultrasonic sensors are key to this device's functionality. They emit sound waves at frequencies beyond human hearing, which then bounce off objects and return to the sensor. By measuring the time taken for these waves to return, the device can calculate the distance to the obstacle, allowing it to alert the user when objects are too close. This non-contact method of detection helps avoid physical strain or injury, making it a significant improvement over traditional canes.

Furthermore, the design is lightweight, compact, and easy to handle, prioritizing user comfort without compromising durability or accuracy. In addition to obstacle detection, this smart stick includes an emergency alarm system, which can be activated by the user if assistance is needed. This feature is particularly useful in cases of falls or other urgent situations, helping draw attention from nearby people.

This project underscores how affordable, accessible technology can create a positive impact for people with disabilities. By combining basic electronic components into a functional and practical tool, this Arduino-based obstacle-detecting stick offers a scalable solution that could be widely adopted in various settings. The device

Proposed Methodology

The design of an Obstacle Detecting Blind Stick using Arduino is highly suitable for addressing the navigation challenges faced by visually impaired individuals due to its reliability, affordability, and adaptability. This design leverages ultrasonic sensors for obstacle detection, which provide an effective and low-cost solution for real-time, non-contact measurement of distances. Ultrasonic sensors are ideal for this purpose because they work well across various surfaces and detect obstacles at different heights, making them well-suited to identifying hazards that a traditional white cane may miss.

Using an Arduino microcontroller as the core of this design enhances its accessibility and customization options. Arduino is both affordable and versatile, allowing for seamless integration of various sensors and feedback components, such as vibrating motors or buzzers that are essential for creating intuitive alerts. Its open-source nature also makes it adaptable, enabling further enhancements like adding GPS or Smartphone connectivity if required.

The haptic and auditory feedback mechanisms in this design make it particularly user-friendly for visually impaired individuals. Vibrations and sounds provide immediate, easy-to-interpret alerts, allowing users to navigate without needing visual input. Additionally, the emergency alarm feature included in this design adds an extra layer of safety, helping users attract assistance in case of unexpected situations.


Overall, this design offers a practical, scalable, and customizable solution that addresses the specific needs of visually impaired individuals


is not only cost-effective but also customizable, allowing for additional features like GPS tracking, Smartphone integration, or adjustable sensitivity to be added as needed. Overall, this project aims to empower visually impaired individuals by providing them with a more advanced tool to navigate their world safely and independently.

for safe and confident navigation in a wide range of environments.

System Architecture:

Figure :System Architecture



Flowchart:*Figure: Flowchart***Code:**

```

const int trigPin = 9; const int echoPin=10;
const int vibrationMotorPin=11; const int buzzerPin
= 12;

```

```

const int distanceThreshold=50; void setup() {
Serial.begin(96000); pinMode(trigPin, OUTPUT);
pinMode(echoPin, INPUT);
pinMode(vibrationMotorPin,OUTPUT);
digitalWrite(vibrationMotorPin, LOW);
digitalWrite(buzzerPin, HIGH);
}
void loop(){
long duration, distance; digitalWrite(trigPin,
LOW); delayMicroseconds(20);
digitalWrite(trigPin, HIGH);
delayMicroseconds(1); digitalWrite(trigPin, LOW);
duration=pulseIn(echoPin,HIGH); distance =
duration * 0.034 / 2; Serial.print("Dist: ");
Serial.print(distance);
Serial.print("cm");
if(distance>0||distance<=distanceThreshold){
digitalWrite(vibrationMotorPin, HIGH);
digitalWrite(buzzerPin, HIGH);
}elseif(distance>distanceThreshold){
digitalWrite(vibrationMotorPin,LOW);
digitalWrite(buzzerPin, LOW);
}
}
delay(10);
}

```

Working:

The **Obstacle and Pothole Detecting Blind Stick** is an assistive device designed for visually impaired individuals, providing both obstacle detection and pothole awareness. The stick uses two ultrasonic sensors, a buzzer, and a vibration motor to deliver timely alerts based on the environment, helping users navigate safely.

1. Ultrasonic Sensors for Obstacle and Pothole Detection

This system employs two ultrasonic sensors (HC-SR04), each with a specific purpose. The first sensor detects obstacles directly in front of the user, and the second sensor is positioned facing downward to detect potholes or sudden drops in the ground.

- **Obstacle Sensor:** The front-facing ultrasonic sensor detects obstacles and calculates the distance to them. When the Arduino triggers the sensor's pulse emission, the pulse travels forward and reflects upon hitting an obstacle. The sensor calculates the time taken for this pulse to return and converts it into a distance reading.
- **Pothole Sensor:** The second ultrasonic sensor is directed towards the ground to measure distance from the surface. If the distance exceeds a set threshold (e.g., 20 cm), it indicates that there is a sudden drop, which could signify a pothole or uneven ground. This reading helps warn the user about potential hazards underfoot.

2. Distance Thresholds and Feedback System

The program uses distinct thresholds to trigger various feedback responses, with specific alerts based on whether the obstacle is nearby or there's a pothole:

- **Obstacle Detection:**
 - **Moderately Close Obstacles (30 cm to 60 cm):** If the obstacle is detected within a range of 30–60 cm, the vibration motor and buzzer activate once every two seconds. This periodic alert warns the user that something is in their path but not immediately close, giving them time to adjust their direction.
 - **Very Close Obstacles (Less than 30 cm):** When an obstacle is detected within 30 cm, the vibration motor and buzzer are activated every second, producing more frequent alerts to prompt the user to stop or turn quickly to avoid a collision.
- **Pothole Detection:**
 - When the downward-facing sensor measures a distance exceeding 20 cm, this implies a sudden

drop in the path, which may indicate a pothole. In this case, the vibration motor and buzzer activate continuously, providing a continuous alert that warns the user to step carefully to avoid a fall or injury.

3. Fail-Safe Mechanism

If neither an obstacle nor a pothole is detected, the buzzer and vibration motor remain off, ensuring that the system is energy-efficient and does not distract the user unnecessarily. This prevents fatigue from false alarms and focuses the user's attention only on genuine hazards.

The Arduino program begins by continuously measuring distances from both the obstacle and pothole sensors. Based on the calculated distances, the program decides which feedback pattern to apply. If an obstacle is detected within 60 cm or a pothole is identified, the system engages the appropriate response through the buzzer and vibration motor.

This layered feedback approach allows users to identify obstacles and potholes with varied intensity, making the device an intuitive and practical mobility aid. The continuous feedback for potholes helps avoid hazards in the ground, while the adjustable alerts for obstacles allow users to manage moderately close or imminent obstacles effectively. This design helps ensure safety and independence for visually impaired users in a variety of environments.

References

- [1] uruvilla, J., Paulose, B., & Sebastian, G. (2016). "Smart walking stick for visually impaired." *International Journal of Engineering Science and Computing*, 6(6), 6350-6353. This paper describes a similar project with a focus on sensor-based alert systems to aid the visually impaired.
- [2] Srivastava, S. (2017). "Smart cane for visually impaired using Arduino and ultrasonic sensor." *International Journal of Research in Engineering and Technology*, 6(6), 2321-7308. Discusses the design and implementation of an ultrasonic sensor-based system to detect obstacles for the visually impaired.
- [3] Ashwini, M., & Arvind, K. (2018). "Smart assistive walking stick for visually impaired using Arduino." *International Journal of Engineering Research and Applications*, 8(5), 75-79. This study explores the use of Arduino and sensors to develop a stick that can detect obstacles and notify the user.
- [4] Gupta, M., & Bansal, D. (2019). "Obstacle detection and pothole detection system for blind using Arduino." *Journal of Emerging Technologies and Innovative Research*, 6(3), 784-789. Describes the use of both obstacle and pothole detection systems integrated into an Arduino-based design.
- [5] Bhavsar, P., & Shinde, S. (2020). "Design of a pothole and obstacle detecting smart stick for visually impaired."

International Journal of Advanced Science and Technology, 29(3), 724-729. Focuses on the design and testing of a smart stick with ultrasonic sensors for detecting potholes and obstacles.

[6] Parihar, P., & Choudhary, R. (2020). "A study on Arduino-based assistive devices for visually impaired." International Journal of Engineering Trends and Technology, 68(4), 100-105. Reviews different Arduino-based assistive devices, including obstacle detection systems, to aid visually impaired users.

[7] Singh, V., & Jha, N. (2019). "Ultrasonic sensor-based obstacle detection system for visually impaired." International Journal of Scientific Research and Review, 7(6), 54-60. Examines various applications of ultrasonic sensors for detecting obstacles, with a focus on systems for the visually impaired.

[8] Khan, A. S., & Farheen, M. (2018). "Assistive smart stick with pothole detection for visually impaired." International Journal of Recent Technology and Engineering, 7(4), 123-128. This study introduces a smart stick that uses ultrasonic sensors to detect both obstacles and potholes.

[9] Sharma, N., & Gupta, R. (2021). "Arduino-based obstacle and pothole detection for navigation aid." Proceedings of the International Conference on Innovations in Engineering and Technology, 123-128. This conference paper explores the practical implementation of a navigation aid with pothole and obstacle detection using Arduino.

[10] Saini, S., & Kumar, M. (2020). "Review on assistive devices for visually impaired using microcontroller." Journal of Engineering Science and Technology Review, 13(1), 124-129. A literature review on various assistive technologies using microcontrollers, focusing on the use of ultrasonic sensors for obstacle detection.

[11] Sundar, S., Sharma, V., & Kumar, R. (2016). Intelligent walking cane for visually impaired individuals using ultrasonic and infrared sensors. *Proceedings of the International Conference on Assistive Technologies and Computing*, 57-64.

[12] Zhao, Z., Chen, Y., & Li, H. (2018). Development of an ultrasonic sensor-based smart cane for blind mobility assistance. *Journal of Accessibility and Design for All*, 8(2), 112-120.

[13] Prakash, R., & Kumar, A. (2017). Low-cost obstacle detection system for blind users using an Arduino-based ultrasonic sensor. *International Journal of Computing and Technology*, 12(1), 19-25.

[14] Ravi, S., & Kumar, R. (2018). Multi-sensor integrated smart cane for blind people: A 360-degree obstacle detection system using ultrasonic sensors. *IEEE Transactions on Human-Machine Systems*, 48(6), 717-723.

[15] Deshmukh, S., & Patil, R. (2019). Development of an ultrasonic-based mobility aid for visually impaired persons. *International Journal of Advanced Robotics and Automation*, 7(3), 102-108.

[16] Nayak, P., Mishra, S., & Patel, R. (2018). Arduino-based smart cane for obstacle detection and real-time feedback. *Journal of Assistive Technology in India*, 13(4), 234-241.

[17] Singh, P., & Patel, P. (2020). An innovative Arduino-based smart cane with ultrasonic sensors for blind navigation. *International Journal of Electronics and Communication Engineering*, 4(5), 55-62.

[18] Raj, A., & Yadav, V. (2021). GPS-based navigation system integrated with object detection sensors for blind people. *Journal of Digital Accessibility Research*, 9(3), 145-151.

[19] Ghosh, S., Das, P., & Biswas, A. (2018). Smart cane for blind people: A hybrid ultrasonic and wireless

communication-based feedback system. *Indian Journal of Engineering and Technology*, 17(7), 99-105.

[20] Choudhury, S., & Saha, A. (2019). Directional vibration feedback system in smart canes for blind navigation. *Journal of Haptic Technology*, 12(4), 35-42.

