



In Hilly Terrain Performance Evaluation of Proactive, Reactive and Hybrid Ad hoc Routing Protocol Using Qualnet for VANET Using Duracell Battery Model

Manish Sharma

Dept. of Physics, Government College Nagrota Bagwan, Himachal Pradesh, India -176047

ABSTRACT: In hilly terrains VANET high speed is the real characteristics which leads frequent breakdown, interference, high noise ratio etc. that further leads to more drainage of the battery. Researchers have elaborated several routing protocols that possess different performance levels. In this paper we studied various Ad hoc routing protocols, Reactive, Proactive & Hybrid, taking in to consideration various VANET parameters like Speed, Altitude etc. in Real traffic Scenario taking battery drainage at the altitude of 1500m. The AODV and DYMO (Reactive), OLSR (Proactive) and ZRP (hybrid) protocols are compared for battery model Panasonic AAA standard using Qualnet as a Simulation tool. Since Energy conservation is main focus area nowadays. Hence performance of the protocols with various battery models counts and helps to make a right selection. Varying parameters of VANET shows that in the real traffic scenarios proactive protocol performs more efficiently for energy conservation leads to minimum drainage.

KEYWORDS: VANET, Routing Protocols, Duracell, Qualnet, Terrains.

I. INTRODUCTION

Vehicular Ad hoc Network (VANET) is a new communication paradigm that enables the communication between vehicles moving at high speeds. It has been found that mobile terminals in fast moving vehicles like cars, buses, trains are frequent signal breakdowns as compared to pedestrians that further leads to more drainage of battery in hilly terrains. Hence in order to improve QoS and energy conservation in fast moving vehicles various light weight routing protocols needed to be studied in Physical and data link layer. So that Right selection of the protocol can be made. There are mainly three types of routing protocols, Proactive [1], Reactive [2], Hybrid [3]. These protocols are having different criteria for designing and classifying routing protocols for wireless ad hoc network. The Mobile Ad hoc Network (MANET) working group of the Internet Engineering Task Force (IETF) [4] develops standards for routing in dynamic networks of both mobile and static nodes[5-6]. The protocols in focus now days are Hybrid protocols and others [7] at higher altitude. Its use in the context of VANET's along with reactive and proactive has always been area under investigation. Routing protocols are always challenging in the fast-moving nodes as their performance degrades and such type of network is difficult to manage as fast handoff, signal quality, Interference maximizes along with other geographical factors, which questions the energy conservations[11-13] i.e. residual battery capacity. Researchers have elaborated several routing protocols that possess different performance levels taking QoS[14,15] as prime concern.

In this work, the feasibility, the performance, and the limits of ad hoc communication using the three types of protocols is evaluated as per battery model Panasonic AAA and Potentials for optimizing the deployed transport and routing Protocols is investigated. The real traffic scenario matches with Dharamshala city of Himachal Pradesh with a location of main Post office and Rain shelter Bus stop. Special care is taken in to provide Realistic scenarios of both road traffic and network usage. This is accomplished by simulating a scenario with the help of simulation tool Qualnet [6]. A micro simulation environment for road traffic supplied vehicle movement information, which was then fed in to an event-driven network simulation that configured and managed a VANET model based on this mobility data. The protocols and their various parameters of the transport, network, data link, and physical layers were provided by well-tested implementations for the networks simulation tool, while VANET mobility is performed by our own implementation. Note that hilly terrain of 1500m is also considered neglecting few geographical constraints.

II. RELATED WORK

Routing protocol is a standard that controls how nodes decide how incoming packets are routed between devices in a wireless domain & further Distinguished in many types. There are mainly three types of routing protocols. AODV (C. Perkins, E. Belding Royer, & S. Das, 2003), DYMO (I. Chakeres, & C. Perkins, 2006) and DSR (D. Johnson, D. Maltz, and Y. Hu, 2004) are the examples of reactive routing protocols whereas OLSR (T. Clausen (Ed.), and P. Jacquet (Ed.) Oct. 2003), TBRPF (R. Ogier, F. Templin, & M. Lewis, 2004) and FSR (M. Gerla, X. Hong, and G. Pei, 2002) are the examples of proactive routing protocols. ZRP (Zone Routing Protocols) STAR are the examples of Hybrid protocol. In our work the chosen protocols are AODV, DYMO, OLSR and ZRP.

A. Ad-hoc on demand vector distance vector (AODV) Routing Protocol

AODV [7] shares DSR's on-demand characteristics in that it also discovers routes on an as needed basis via a similar route discovery process. However, AODV adopts a very different mechanism to maintain routing information. It uses traditional routing tables, one entry per destination. This is in contrast to DSR, which can maintain multiple route cache entries for each destination. Without source routing, AODV relies on routing table entries to propagate an RREP back to the source and, subsequently, to route data packets to the destination. AODV uses sequence numbers maintained at each destination to determine freshness of routing information and to prevent routing loops. All routing packets carry these sequence numbers.

B. Dynamic MANET On demand (DYMO) Routing Protocol

DYMO is another reactive routing protocol that works in multi hop wireless networks. It is currently being developed in the scope of IETF's [4] MANET working group and is expected to reach RFC status in the near future. DYMO is considered as a successor to the AODV routing protocols. DYMO has a simple design and is easy to implement. The basic operations of DYMO protocol are route discovery and route Maintenance was studied extensively [8] along with comparison of two on demand routing protocols.

C. Optimized Link State Routing (OLSR) Protocol


OLSR [9] is the proactive routing protocol that is evaluated in this synopsis. Basically OLSR is an optimization of the classical link state algorithm adapted for the use in wireless ad hoc networks. In OLSR, three levels of optimization are achieved. First, few nodes are selected as Multipoint Relays (MPRs) to broadcast the messages during the flooding process. This is in contrast to what is done in classical flooding mechanism, where every node broadcasts the messages and generates too much overhead traffic.

D. Zone Routing Protocol (ZRP)

Hybrid routing combines characteristics of both reactive and proactive routing protocols to make routing more scalable and efficient [10]. Mostly hybrid routing protocols are zone based; it means the number of nodes is divided into different zones to make route discovery and maintenance more reliable for MANET. The need of these protocols arises with the deficiencies of proactive and reactive routing and there is demand of such protocol that can resolve on demand route discovery with a limited number of route searches. ZRP limits the range of proactive routing methods to neighbouring nodes locally; however ZRP uses reactive routing to search the desired nodes by querying the selective network nodes globally instead of sending the query to all the nodes in network. ZRP uses "Intrazone" and "Interzone" routing to provide flexible route discovery and route maintenance in the multiple ad hoc environments. Interzone routing performs route discovery through reactive routing protocol globally while intrazone routing based on proactive routing in order to maintain up-to-date route information locally within its own routing range. The overall characteristic of ZRP is that it reduces the network overhead that is caused by proactive routing and it also handles the network delay that is caused by reactive routing protocols and perform route discovery more efficiently. Normal routing protocols which works well in fixed networks does not show same performance in mobile ad hoc networks. In these networks routing protocols should be more dynamic so that they quickly respond to topological changes. There is a lot of work done on evaluating performance of various MANET routing protocols for constant bit rate traffic.

III. BATTERY MODELS

The zinc/potassium hydroxide/manganese dioxide cells, commonly called alkaline [16] or alkaline-manganese dioxide cells, have a higher energy output than zinc-carbon (Leclanche) cells. Other significant advantages are longer shelf life, better leakage resistance, and superior low temperature performance. In comparison to the zinc-carbon cell, the alkaline cell delivers up to ten times the ampere-hour capacity at high and continuous drain conditions, with its performance at low temperatures also being superior to other conventional aqueous electrolyte primary cells. Its more effective, secure seal provides excellent resistance to leakage and corrosion. The use of an alkaline electrolyte, electrolytically prepared manganese dioxide, and a more reactive zinc powder contribute to a higher initial cost than zinc-carbon cells. However, due to the longer service life, the alkaline cell is actually more cost-effective based upon cost-per-hour usage, particularly with high drains and continuous discharge. The high-grade, energy-rich materials composing the anode and cathode, in conjunction with the more conductive alkaline electrolyte, produce more energy than could be stored in standard zinc carbon cell sizes. In comparison to the zinc-carbon cell, the alkaline cell [17] delivers up to ten times the ampere-hour capacity at high and continuous drain conditions, with its performance at low temperatures also being superior to other conventional aqueous electrolyte primary cells. Its more effective, secure seal provides excellent resistance to leakage and corrosion. The product information and test data included in this section represent Duracell newest alkaline battery products.



Dimensions	Millimeters	Inches
A Max	44.5	1.752
B Min	43.5	1.713
C Min	4.3	0.169
F Max	3.8	0.150
G Min	0.8	0.031
OD Max	10.5	0.413
OD Min	9.5	0.374

Fig.1 Industry Standard Dimensions mm(inches)

Table 1. Alkaline battery Parameters

Nominal Voltage:	1.5 V
Operating Voltage	1.6 - 0.75V
Impedance:	136 m-ohm @ 1kHz
Typical Weight:	0.38mg(11.0oz)
Typical Volume:	3.8 cm ³ (0.2 in. ³)
Storage Temperature Range	-20°C to 35°C
Operating Temperature Range:	-20°C to 54°C
Terminals:	Cap & Base
ANSI:	24A
IEC:	LR03

IV SIMULATION TOOL

The collaboration of imminent research objectives and its related scope in this study are also collapsed into same influence of simulation environment for generating some authenticated outcomes. For this purpose, the adopted methodology for the results of this research work (specifically comparative routing analyses) is based on simulations near to the real time packages before any actual implementation.

QualNet is a comprehensive suite of tools for modelling large wired and wireless networks. It uses simulation and emulation to predict the behavior and performance of networks to improve their design, operation and management. QualNet enables users to Design new protocol models, optimize new and existing models, Design large wired and wireless networks using pre-configured or user-designed models, Analyze the performance of networks and perform what-if analysis to optimize them. QualNet (6) is the preferable simulator for ease of operation. So, we found QualNet be the best choice to implement our scenarios as we do not need every feature possible, just those for the token passing and message routing. QualNet is a commercial simulator that grew out of GloMoSim, which was developed at the University of California, Los Angeles, UCLA, and is distributed by Scalable Network Technologies [6]. The QualNet simulator is C++ based. All protocols are implemented in a series of C++ files and are called by the simulation kernel. QualNet comes with a java based graphical user interface (GUI). Qualnet is simulator by scalable network technologies having versatile applications in data communication systems. It is a network planner to create virtual models of all types of data , voice and video networks that behaves as real communication network.

Table2. Simulation Parameters

Simulator	Qualnet Version 5.o.1
Terrain Size	1500 x 1500
Simulation time	3000s
No. Of Nodes	15
Mobility	Random Way Point Pause time= 0s
Speed of Vehicles	Min.=3m/s Max.=20m/s
Routing Protocols	AODV,DYMO,OLSR,ZRP
Medium Access protocol	802.11 MAC, 802.11 DCF Tx Power=150dbm
Data size	512 bytes
Data Interval	250ms
No. of sessions	5
Altitude	1500
Weather mobility model	100ms
Battery models	Panasonic AAA

V. DESIGNING OF SCENARIO

The scenario is designed in such a way that it undertakes the real traffic conditions. We have chosen 15 fast moving vehicles in the region of 1500X1500 with the random way point mobility model. There is also well defined path for some of the vehicles, so that real traffic conditions can also be taken care of. It also shows wireless node connectivity of few vehicles using CBR application. The area for simulation is Hilly area with altitude of 1500 meters. Weather mobility intervals is 100ms. Pathloss model is two ray with max prop distance of 100m. The real traffic scenario matches with Dharamshala city of Himachal Pradesh with a location of main Post office and Rain shelter Bus stop.




Figure2. Qualnet VANET Scenario

The simulation result brings out some important characteristic differences between the routing protocols. In all the simulation results ZRP outperforms the other protocols. This is because ZRP is a hybrid protocol and it pre determines the route in well defined manner along with its on demand nature. It uses destination sequence numbers to ensure loop freedom at all times and it offers quick convergence when the network topology changes. OLSR appear as the second best of these having some common proactive characteristics.




Fig. 3 Battery model comparison for Various Protocols

IV. CONCLUSION AND FUTURE WORK

The simulation results showed that the proposed ZRP is a hybrid protocol and it pre determines the route in well-defined manner along with its on-demand nature. It uses destination sequence numbers to ensure loop freedom at all times and it offers quick convergence when the network topology changes. We have used very small network of 15 nodes, as number of nodes increases the complexity will increase, which may affect the performance of hybrid routing protocols. We can increase the mobility, data size, altitude, number of nodes and analyze the performance.

REFERENCES

1. Tony Lason & Nicklas Hedman(1998) "Routing protocols in wireless Ad hoc network" Lulea university of technology, Stockholm.
2. Christoph Sommer & Falko Dressler(2009) "The DYMO Routing Protocol in VANET Scenarios" University of Erlangen-Nuremberg, Germany.
3. Bilal Mustafa & Umar Waqas Raja(2010) "Issues of Routing in VANET" School of Computing at Blekinge Institute of Technology.
4. IEEE, "Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specifications(1997)," IEEE Std. 802.11-1997,.
5. Behrouz A. Forouzan(2008) Data communications and Networking, Networking series, Tata Mcgraw-Hill publishers.
6. "Qualnet simulator version 5.0.1", Scalable Network Technologies, <http://www.scalable-networks.com/>
7. Inmran Khan(2009) "Performance evaluation of Ad hoc routing protocols for Vehicular ad hoc networks" Mohammad Ali Jinnah University
8. C. Perkins & E. Royer & S. Das, & K. Marina(2001), "Performance comparison of two on-demand routing protocols for ad hoc networks," in IEEE Personal Communications..
9. Lee Kok Thong(2004) "Performance analysis of mobile adhoc routing protocols" thesis Naval post graduate college , Monterey, California.
10. Srivastava, A., Prakash, A., & Tripathi, R. (2020). Location based routing protocols in VANET: Issues and existing solutions. Vehicular Communications, 23(1), 1–30.
11. Tanuja, K., Sushma, T. M., Bharathi, M., & Arun, K. H. (2015). A survey on VANET technologies. International Journal of Computer Applications, 121(18), 1–9.
12. Cunha, F., Villas, L., Boukerche, A., Maia, G., Viana, A., Mini, R. A. F., et al. (2016). Data communication in VANETs: Protocols, applications and challenges. Ad Hoc Networks, 44, 90–103.

13. Kaur, S., Aseri, T. C., & Rani, S. (2017). Qos aware routing in vehicular ad hoc networks: A survey. *International Journal of Computer & Mathematical Sciences*, 6(4), 1–6.
14. Zeeshan, S., Zafar, Q. A. B., & Haseeb, M. (2018). Qos in vehicular ad hoc networks—A survey. *Journal of Information Communication Technologies and Robotic Applications*, 9(1), 48–58.
15. Yuying, W., & Zheng, J. (2020). Modeling and analysis of the downlink local delay in MEC-based VANETs. *IEEE Transactions on Vehicular Technology*, 69(6), 6619–6630.
16. <http://www.duracell.com/>
17. <http://www.panasonic.com/industrial/batteries-oem>

