



INTERNATIONAL JOURNAL OF CREATIVE RESEARCH THOUGHTS (IJCRT)

An International Open Access, Peer-reviewed, Refereed Journal

Smart And Secure Urban Environment Monitoring Using Wireless Sensor Networks

Dr. Rashmi S Bhaskar¹

Associate Professor, Department of Electronics and Communication Engineering, BNMIT, Bengaluru, Karnataka, India

Sujaya B L²

Assistant Professor, Department of Electronics and Communication Engineering, BNMIT, Bengaluru, Karnataka, India

Dr. Vrunda Kusanur³

Associate Professor, Department of Electronics and Communication Engineering, BNMIT, Bengaluru, Karnataka, India

Abstract—Wireless Sensor Network has been increasingly used for remote monitoring system and its adoption in increasing exponentially for larger application too. However, there are various challenges associated with both resource management and security that roots up when the deployment scale goes massive and distributed in order. The proposed system considers a case study of smart city management where the problems associated with data transmission and security has been addressed. This is carried out using the provisioning of urban environment monitoring system that is an essential system for smart city projects to assure the citizens' better-quality well-being. The scalable and effective urban environment monitoring system requires a seamless transmission of the data from the sensor nodes to the analytics engine. The existing architectures are more designed to suit very specifically the use-cases. As a contribution, the proposed system introduces a cost-effective architecture for environmental monitoring in urban zones of smart city named as a Smart Sensor Surveillance System (4S- UEM). The core idea of the proposed system is to offer a balance between resource efficiency and resilience secure communication in large scale deployment of WSN considering smart city as deployment and assessment area. The proposed system makes use of urban geographical clustering process in order to develop an organized structure of sensor nodes. Different from any existing studies, the proposed system introduces data analytical engine followed by secure routing using gateway. The design of the proposed system is carried out using layered architecture of the communication model targeting towards a cost-effective, energy optimal, and secure data transmission to the analytics engine.

Keywords—Wireless sensor network (WSN), Urban environment monitoring (UEM)

I. INTRODUCTION

Urban environment monitoring (UEM) is an essential requirement for smart city projects [1] [2] [3] for various control mechanism applications. All these applications require a Smart Sensor Surveillance System abbreviated as '4S'. There exist multiple technologies for setting up surveillance systems for acquiring the data of importance. The analytics of these data correlates with the environmental changes [4]. Such technologies include surveillance camera systems and ambient-based monitoring technologies that suffer scalability, reliability, and the efficient correlation among spatial-temporal information [5]. The use of wireless sensor networks (WSN) as: "4S for UEM," i.e., "Smart Sensor Surveillance System for Urban Environment Monitoring," aims to overcome these challenges and limitations. Therefore, this research study aims to design a standard architecture of WSN that provides a generalized architecture to comply with the "4S for UEM" requirements. The rationale behind arriving at a classic WSN for various 4S-UEM applications is overcoming the bottlenecks of the limitations of the suitability of one application-specific architecture to another. Typically, the data acquisition and analysis of many environmental parameters that include: temperature, humidity, traffic density on the road, vibration exerted on public infrastructure, pH-values in water, and many more parameters which leads to building smart control system for smart home, transportation, the safety of building & bridges, and water quality management, etc. as an actual application required for the smart city projects. Fig. 1 provides a snap-view of "4S-UEM" based applications and the intrinsic requirement. As seen in Fig. 1, the intelligent system based on the architecture of the 4S-UEM requires four essential characteristics to be met by the suitable design of the 4S-UEM, and those characteristics are: {Lifetime, Accuracy, Coverage, Reliability}. Another additional requirement apart from these four is secure communication so that the realization of the 4S-UEM applications become possible in a real-time context. This paper proposes analytical modeling of the design of secure transmission through 4S-UEM to ensure accurate, reliable, and secure communication with optimal coverage.

II. REVIEW OF LITERATURE

This section describes various related work of design and development of the WSN based applications for assessing the methodological briefing of existing urban environment monitoring system (UEMS). The scope of the discussion is only limited to various resource optimization scheme which are considered as best scheme for resource management. It is because if the resource management is enhanced, eventually security scheme will be positively affected. The typical challenge in the UEMS faced is the issue of the optimal deployment of the sensor nodes that ensure maximum coverage and another is the secure communication. To provide a connecting link for transmission, a network of wireless sensor nodes is formed where a hierarchy of nodes as hop nodes, local and global sink nodes are the integral part of the WSN as static or dynamic WSN [6] depending upon the mobility of nodes and application requirements.

It is essential to consider a better network performance while designing the network deployment strategy with optimal coverage and connectivity [7]. The problem of the optimal coverage is formulated either as a greedy algorithm [8] or an integer optimization problem [9], which resembles the localization or placement problem of the facilities [10]. The sensor nodes' optimal numbers are computed using various methods like disk model, sector model, and geometry pattern model [11]. Whereas if the localization is known, then the problem of the optimal deployment in the Urban area of monitoring and deployment of WSN prefer an integer programming where popular method like i) divide-and-conquer, ii) simulated annealing, and iii) Genetic Algorithm, but these methods pose additional overhead of time complexity [12]. Irrespective of these methods, there exist some unique challenges for the deployment of the WSN for UEMS. Another important observation is that in most of the deployment, the base station's position is always fixed, which does not provide an optimal network performance [13]. There is no doubt that there are many research work being carried out towards secure routing in WSN with evolution of different methodologies and techniques. The existing methods are found to offer highly specific issue addressing scheme overlooking different challenges associated with the addressed issues. For an example, secure scheme cannot be only addressed using encryption but it equally demands resource management. Existing studies witness few direction of work aim like this integrated issue. Hence, the prominent research gap explored is that there are few studies which have linked practical energy retention with cost effective secure data aggregation in WSN considering challenging distributed and large scale area.

Intelligent System	Pollution Control	Performance Metric	Reliability
	Disaster Management		
	Public Safety		Coverage
	Electricity Grid		
	Infrastructure Health		Accuracy
	Water-Supply & Waste Water		
	Transportation		Lifetime
	Smart Sensor Surveillance System for Urban Environment Monitoring (4S-UEM)		

Fig. 1. 4S-UEM based Applications




Fig. 2. Generalized Architecture 4S-UEM

III. SYSTEM MODEL FOR UEM

To monitor the urban environment, changes concerning temperature (T), pollution (CO₂), and environmental parameters are significant for the meteorological department. The applications ranging from dairy farm monitoring to traffic management can be built on a generalized architecture: 4S- UEM, as in Fig. 2.

A. Sensor Node and Data Analytics Engine Deployment

An essential parameter in this part of implementation is basically number of sensors and simulation area. Introducing a data analytic engine is another contribution of proposed system which processes and analyzes the aggregated data unlike any existing clustering approach. The sensor nodes (Sn) are uniformly randomly distributed across a geographical area ($A=L \times L$) of deployment in the region to monitor urban locality. An explicit algorithm-1 ensures the optimal coverage and connectivity while deploying the sensor nodes (Sn), local gateway (Lg), and data analytics engine (DaE) as intrinsic units of 4S-UEM. The Sn's deployment is modeled as a graph: $G(V)$, where V is the vertex or a point that represents a Sensor node Sn.

Algorithm-1: Intrinsic unit deployment of 4S-UEM

Input: n, L, DaE **Output:** $G(V)$ **Process:**
Start
 for $\forall Sn_k \in n$ [$Sn.x, Sn.y$] \leftarrow frand(n) \times L
 $G(V1) \leftarrow f([Sn.x, Sn.y])$ Initialize, {DaE.x, DaE.y}
 $G(V2) \leftarrow f(\{DaE.x, DaE.y\})$ $G(V) \leftarrow G(V1) \cup G(V2)$
End

The WSN typically consists of 'n' number of sensor nodes (Sn) so that any sensor node ('Sn')_k $\in n$, s.t $2 \leq n$, where $n \in \mathbb{N}$ as a positive integer. The model takes 'n' and 'L' and DaE as independent variables to get $G(V)$ as the dependent variable, i.e., $G(V) \leftarrow f(n, L, DaE)$. The adjustment of connectivity and coverage of Sn and DaE for optimization takes place with variations in its localization coordinates of Sn and DaE as ($[Sn.x, Sn.y]$) and {DaE.x, DaE.y} respectively. The normalization of a logical layer of the architecture of the 4S- UEM is as in the Fig. 3, while the model imitates the process of deployment.




Fig. 3. Normalized Model Imitation for G(V) Sensor Node of 4S-UEM into an Urban Cluster




Fig. 4. Membership to each

B. Urban Geographical Clustering

In the smart city projects, the 4S-UEM synchronizes with the many sensor nodes deployed across the city or urban region by introducing an algorithm for Urban Geographical Clustering (UGC) to meet layer-wise communication that distance of communication is reduced. The prominent parameter of this part of implementation is local gateway which is responsible for performing translation services. The very basic requirement of UGC is to select a randomized local gateway (Lg) such that $Lg \in \{Sn\}$. A probabilistic approach considering the node's energy and the boundary conflict to avoid overlapping of spatial data overload is considered for the designing of UGC and selection of Lg. A straightforward process for the UGC is as in the algorithm 2. This approach establishes the communication between the lower layer of the sensor nodes or actuator with the local gateway.

number of urban clustering, which is taken as a set: $nC = \{m^2\}$, where $m \in$ a positive integer number. The nC is finally decided based on the node with energy and a probabilistic approach, where the boundary constraint \vec{B} . To compute B_c , initially, the difference of number of local gateways (nLg) and $nCas\vec{D}$ is computed as in equation 1.

$$\vec{D} = |(nC - nLg)| \quad (1)$$

Then, the index (Id) and minimum value (Vmin) from \vec{D} along with area component L goes to an explicit function to define the boundary as \vec{B} , which is a linearly spaced vector of L into Id+1 component, and the nC assigns as Id^2 . Further, a series \mathcal{S} as 1 to nC reshaped to the number of row and number of columns as \sqrt{nC} , say if $nC = 16$, then the \mathcal{S} is as below:

$$\mathcal{S} = \begin{bmatrix} 1 & 5 & 9 & 13 \\ 2 & 6 & 10 & 14 \\ 3 & 7 & 11 & 15 \\ 4 & 8 & 12 & 16 \end{bmatrix} \quad (2)$$

To get the membership of $\star Sn$ into a specific urban cluster, the localization of each $(Sn)_i \in n$ is taken as basic parameters to define its class membership with the respective urban cluster based on the condition with the boundary constraints \vec{B} as in equation 3.

$$(\Sigma v)_i \cdot \xi \in \vec{B}_i \perp (\Sigma v)_i \cdot \xi < \vec{B}_{i+1} \perp (\Sigma v)_i \cdot \psi \in \vec{B}_i \perp (\Sigma v)_i \cdot \psi < \vec{B}_{i+1} \quad (1)$$

The corresponding identity to all the Sn is designated as cluster-id (Cid), with a potential of equal probability to be a Lg, and in this way, the urban clustering of all sensor nodes.

Algorithm-2: Urban Clustering for 4S-UEM

Input:G(V) **Output:**Cid, Lg *Process:*

Start

Initialize, $nC \leftarrow \{m^2\}$, where $m \in N$

$$\vec{D} = |(nC - nLg)|$$

$$[Vmin, Id] \leftarrow fmin(\vec{D})$$

$$\vec{B} \leftarrow fbound(id, L)$$

$$nC \leftarrow Id^2$$

$S = 1$ to nC with step 1

$S \leftarrow \text{freshape}(S, \sqrt{nC} \cdot \sqrt{nC})$

for membership of $\star S_n$ into an urban-Cluster if takes place, as seen in Fig. 4.

Section C describes the procedure for Lg selection along with the secure routing process as in Algorithm 3.

C. Secure Routing through Selected Local Gateway to the DaEin 4S-UEM

The very objective of the optimality of the architecture of the 4S-UEM is to meet the energy balance of the nodes as well as the network with the consideration of the optimal routing in the least consumption of energy as well the mitigation capacity for the data integrity against any kind of attacks which ensure the reliability of the data delivery for the analytics engine to provide the correct analysis on the real-time basis.

$(S_n)_{i,x} \geq \bar{B}_i^x \wedge (S_n)_{i,x} < \bar{B}_{i+1}^x \wedge$

$(S_n)_{i,y} \geq \bar{B}_i^y \wedge (S_n)_{i,y} < \bar{B}_{i+1}^y$

update: Cid for $\star S_n$

end

visualize the urban

clustering Call algorithm

for selection of Lg

Update: Lg in each communication cycle

End

The very basic assumption made while designing the architecture of 4S-UEM is that the number of local gateways (Lg) is as equal to the number of zones in the city or urban geographical region under monitoring i.e. $Lg = nC$, where $nC =$ number of clusters

Algorithm-3: Local Gateway selection in the Cluster of 4S-UEM and Secure Routing

Input: nC **Output:** LgProcess:

Start

Initialize the values of each in set:

$P = \{Pl, cPl, Etx, ERx, Efs, Eamp, Ea, \}$

Setup process:

Initialize P_n

$P_o \leftarrow R_{n1} \times P_n$ $P_{kc} \leftarrow R_{n2} \times P_n$ Generation of CG

$[CG1, CG2] \leftarrow \text{farbitrary}(P_n, ID)$ Lg Selection process:

Initialize $\star S_n$ $P(S_n | Lg \rightarrow p \%)$

second stage of the system is the selection process of the Lg.

- **Local Gateway Selection Process:** In the Lg section's typical process, the S_n 's energy plays a predominant role. The model validations occur with the varying probability of being Lg such that for $\star S_n$ having $P(S_n$

$| Lg \rightarrow p \%)$. Further, the cluster-id (uCID) for $\star uC$ and the S_n whose energy $(E) < 0$ is marked as a node as fault or dead node ID as (DSn) and the total number of such dead nodes = $nDSn = \sum DS_n$. Therefore, the sensor nodes S_n in each cycle of communications to be considered as the nodes with some energy as $(ASn) = nS_n - nDS_n$ is only considered to be set of the eligible Lg: $Lg: \rightarrow \{ASn\}$. The selection of the Lg from the set of $\{ASn\}$ takes place based on a threshold node (Th) as in equation

$ASn \leftarrow (nS_n - nDS_n)$ $Lg \leftarrow G(ASn)$ based on Th

$Th \leftarrow \frac{p-1}{p} [Ccxmod()$

Call data authentication process (Algorithm -4)

Transfer the packets after integrity authentication to DaE

End

The system models take a set of parameters as independent variables, $P = \{Pl, cPl, Etx, ERx, Efs, Eamp, Ea, \}$, where: $Pl =$ size of the data packet, $cPl =$ size of the control packet, Etx and ERx are energy required for transmission and receiving respectively. Here Efs and $Eamp$ are the respective amplification energy in case of free space communication or dense network deployment, whichever is the case. In many of the current work,

it is found that, while designing the architecture of the communication over wireless sensor network, only a basic first radio model is considered with the transmission and amplification energy into consideration [14]. Whereas the system model of 4S-UEM also considers the energy required for the data to be aggregated or fused at the respective $L_g \in uC$ (urban cluster) in the set of P , the performance resembles to the real-time constraints or context.

The characteristic of the sensor nodes (S_n) is a low capacity of computation and memory; thus, a lightweight security mechanism is proposed in the architecture of the 4S-UEM for the data authentication process in line with customized elliptical curve cryptography (ECC), while layer-wise communication. The first stage of this procedure is the setup stages as below:

- *Setup process:* In this process, the prominent parameter is a prime number (P_n) initiates to get the value of a primal P_o as a product of a random number (R_{n1}) and the P_n and a public key center (P_{kc}) as $R_{n2} \times P_n$, where R_{n2} is another random number. An explicit function: $farbitrary()$ is designed to take the P_n and the ID as an input argument to get the cyclic group. This operation's very basic function is to produce two cyclic groups (CG): $\{G_1, G_2\}$ with a single element P_n such that it produces a set of the invertible values with a single binary operation of property associative.

If the $T_h < a$ random number between '0' and '1', the $S_n \in A_{S_n}$ is treated as L_g from a group of $G(S_n)$. In the equation 4, $p =$ probability % of the A_{S_n} to be L_g , $C_c =$ current communication iteration, $G(S_n) = \star S_n \in A_{S_n}$ that has not been chosen as L_g in the last $(1/p)$ communication iteration. This threshold (T_h) is considered in the state of artwork for hierarchical communication LEACH and its variance [15][16]. Unlike any another traditional approach, the rest of the S_n receives the broadcasted cPI and decides to be part of this L_g based on the energy-based signal strength. The communication process further in the 4S-UEM communication process goes for the data authentication, aggregation then transmission to the DaE as described into the algorithm -4. Fig. 5 illustrates the current stage as S_n , DaE, and urban clustering and selection of the L_g .

It is essential to integrate a data-authentication process in communication to ensure the correctness of the data reaching the DaE, so that correct analysis of the data of the environments records provides accurate input or instructions to the control systems. However, the trade-off here is to handle the timely delivery in optimal energy way as the sensor data collected from the various uC takes some amount of energy that influence the overall network lifetime.





Fig.5.Selection of Local Gateway (L_g) in the Urban Cluster of 4S-UEM Fig 6.The Transmission Process of Messages from uC through L_g to DaE of 4S-UEM.

The unique characteristics of the proposed communication process in the layer-wise approach of data from the individual sensors to the respective L_g and the aggregated or fused data transmission to the DaE in the optimal energy way even if the data gets authenticated by a very lightweight hashing mechanism of data integrity check within the sleep schedule cycle of the S_n , L_g , and DaE to avoid any kind of the collision, which is our future research direction to design an optimal tree-based routing for the channel resource allocation, which is beyond the scope of this stage of the architecture design. The details of the algorithm-4 are as below:

Algorithm-4: Data authentication, Aggregation, and transmission to the DaE as 4S-UEMSecure Routing procedure

Input: nC

Output: Lg

Process:

Start

Initialize, Id of Lg , and Id of ASn

$\star ASn \in uC$, record messages as dP

$q \leftarrow fhash-1(Id-ASn, Pn)$

$[q, Pk] \leftarrow fkeygen(Id-ASn, Rn1)$ *Initialize, Signing operation*

Generate a $Rn3$

$P1 = Rn3 \times Pn$

$q1 \leftarrow fhash-2(P1, Id-ASn, dP)$ $u1 \leftarrow \sum [Pk, (Rn3 \times q1)]$ *Update: Signature*

$Sig \leftarrow \{P1, u1, Id-ASn, dP\}$ $sAm \leftarrow \sum mT \times \sum u1$

$CG \star Lg$: mark $Lg \rightarrow 1$ based on ThAggregation Verification:

Call SPR

End

In this process, the Id of $\star Lg$ gets initialized, and for each uC , Initially, the Id of $Sn \in$ respective Lg is used for finding the ASn , and further, $\sum(ASn)$ participates in transmitting their data to the Lg for the aggregation process of the data packets. The secure aggregation process includes Lg selection, Sn data generation, signature verification, and routing simultaneously.

For $\star ASn \in uC$, the respective data packet (dP) depends upon the application used in a signing process. An explicit function $fkg()$ takes the Id of ASn and $Rn1$ as used while creating the cyclic group in algorithm 3. The process of message authentication uses hashing algorithm in the key generation based on Id of ASn and $Rn1$, where $fhash-1(Id-ASn) \rightarrow q$, where $q = Pn \times Id-ASn$, which finally provides corresponding private key (Pk) for ASn using $Pk = Rn1 \times q$ using an explicit function $fkeygen()$. The next operation is the Signing operation, which takes $\{Id-ASn, dP, Pn, Pk\}$. Initially, a random number $Rn3$ is generated in the signing process, which gives a first $P1$ as $P1 = Rn3 \times Pn$, which passes into $fhash-2()$, along with $Id-ASn$ and dP , which gives a new hash value $q1$ as $q1 = dP \times Id-ASn \times P1$. Another, primal $u1$ is computed as in equation 5.

$$u1 = \sum [Pk, (Rn3 \times q1)]$$

Finally, the signature set includes $\{P1, u1, Id-ASn, dP\}$ and each intermediate computation stores in message-term (mT) as $u1 \times Pkc$, where Pkc comes from algorithm 3. Finally, $\sum mT \times \sum u1$ assigns as a signature for aggregate messages at $Lg(sAm)$.

The cyclic group values of for $\star Lg$ which do not participate in the selection, and the flag is set to zero for all Lg , and the process continues with the comparison of a random number between 0-1 and the Th as in equation 4. Finally, the aggregation verification occurs, and the system calls for the shortest path routing either from Lg to DaE or as inter Lg routing. Fig. 6 illustrates the data transmission process of the proposed 4S-UEM.

Fig. 6 clearly illustrates two layers of data transmission as proposed in 4S-UEM. The first layer of transmission takes place between sensor nodes (Sn) to the Local gateway (Lg) and the second layer of transmission takes place between the Lg to the data analytics engine (DaE). In Section 4, observations of energy variation and the network life are described to understand the model's behavior while imitating in a sequential numerical computation platform.

IV. PERFORMANCE EVALUATION

There are two scenarios to validate the model, and these scenarios are 1) Traditional [6]-[13] and proposed approach of data communication without the data aggregation process and 2) Traditional and proposed approach of data communication with data aggregation process. Fig. 7 to 11 represents the graphical representation of numerical outcomes in Tables I to V with an intention towards assessing scalability. The outcomes are represented in the form of energy parameters on y-axis with increasing number of sensors to represents the influence of performance parameters. The outcome shows proposed system with better energy compared to existing approach.

TABLE I. FIRST NODE DEATH AT NUMBER OF URBAN CLUSTERS = 4
FIRST NODE DEATH AT NUMBER OF URBAN CLUSTERS = 9

No. of Nodes/ M	M1	M2	M3	M4
100	245	204	264	274
200	259	242	311	313
300	269	245	320	301
400	260	221	316	293
500	284	218	327	313

TABLE II.

No. of Nodes/ M	M1	M2	M3	M4
100	106	123	117	170
200	240	119	259	225
300	250	142	289	224
400	262	151	309	203
500	261	142	312	209

TABLE III. FIRST NODE DEATH AT NUMBER OF URBAN CLUSTERS = 16

TABLE IV. FIRST NODE DEATH AT NUMBER OF URBAN CLUSTERS = 25

No. of Nodes/ M	M1	M2	M3	M4
100	80	39	80	82
200	103	99	82	69
300	85	110	150	107
400	167	118	228	100
500	210	110	246	104

No. of Nodes/ M	M1	M2	M3	M4
100	81	39	86	60
200	131	99	190	108
300	210	110	242	137
400	237	118	272	145
500	249	110	285	149

TABLE V. FIRST NODE DEATH AT NUMBER OF URBAN CLUSTERS = 36

No. of Nodes/ M	M1	M2	M3	M4
100	79	23	80	29
200	80	35	83	44
300	86	52	88	59
400	144	37	131	73
500	178	60	156	72

V. CONCLUSION

The unified architecture proposed in this paper is named 4S-UEM, keeping in mind that to deploy a smart monitoring system for the urban environment monitoring purpose, the entire region of the urban zone is divided into the urban clusters where a local gateway is chosen smartly and intelligently. The local gateway collects the data and sends the data either directly or through inter-local gateway routing with the data verification provisioning. The important findings of this paper are i) proposed system offers approximately 47-58% of energy conservation over a large network of smart city, ii) The clustering model suits well with the public key encryption mechanism implemented unlike any existing methods, iii) the study offers no iterative scheme towards optimizing resources and hence it is highly cost effective. The 4S-UEM model provides a consistent result in terms of the network lifetime with a varying number of node density and the cluster. This work's future direction is to evolve a routing model so that priority-based routing takes place with further

energy optimization during the channel allocation and avoidance of the collision of the packets utilizing optimal timeslot scheduling of the radio.

VI. REFERENCES

- [1] "The Smart City Building Blocks & Their Synergy with Smart Villages", <https://www.ieeeottawa.ca/2020/08/the-smart-city-building-blocks-their-synergy-with-smart-villages/>, August 2020.
- [2] Z. Lv, B. Hu and H. Lv, "Infrastructure Monitoring and Operation for Smart Cities Based on IoT System," in *IEEE Transactions on Industrial Informatics*, vol. 16, no. 3, pp. 1957-1962, March 2020, doi: 10.1109/TII.2019.2913535.
- [3] Z. Zhao, J. Wang, C. Fu, D. Liu, and B. Li, "Demo Abstract: Smart City: A Real-Time Environmental Monitoring System on Green Roof," 2018 IEEE/ACM Third International Conference on Internet-of-Things Design and Implementation (IoTDI), Orlando, FL, 2018, pp. 300-301, doi: 10.1109/IoTDI.2018.00049.
- [4] R. Du, P. Santi, M. Xiao, A. V. Vasilakos and C. Fischione, "The Sensable City: A Survey on the Deployment and Management for Smart City Monitoring," in *IEEE Communications Surveys & Tutorials*, vol. 21, no. 2, pp. 1533-1560, Secondquarter 2019, doi: 10.1109/COMST.2018.2881008.
- [5] U. Gil, I. Pena, D. Guerra, D. de la Vega, P. Angueira and J. L. Ordiales, "Statistical Characterization of Medium Wave Spatial Variability Due to Urban Factors," in *IEEE Transactions on Antennas and Propagation*, vol. 59, no. 9, pp. 3498-3500, Sept. 2011, doi: 10.1109/TAP.2011.2161550.
- [6] A. S. Alkalbani and T. Mantoro, "Security comparison between dynamic & static WSN for 5g networks," 2017 Second International Conference on Informatics and Computing (ICIC), Jayapura, 2017, pp. 1-4, doi: 10.1109/IAC.2017.8280615.
- [7] J. N. Al-Karaki and A. Gawanmeh, "The Optimal Deployment, Coverage, and Connectivity Problems in Wireless Sensor Networks: Revisited," in *IEEE Access*, vol. 5, pp. 18051-18065, 2017, doi: 10.1109/ACCESS.2017.2740382.
- [8] Saadi, N., Bounceur, A., Euler, R. et al. Maximum Lifetime Target Coverage in Wireless Sensor Networks. *Wireless PersCommun* 111, 1525–1543 (2020). <https://doi.org/10.1007/s11277-019-06935-5>.
- [9] Zamani, M., Rezaei, A. & Farzinvas, L. Two-phase node deployment for target coverage in rechargeable WSNs using genetic algorithm and integer linear programming. *J Supercomput* (2020). <https://doi.org/10.1007/s11227-020-03431-7>.
- [10] Wenfeng Zhou and Zhenping Li, "The multi-covering emergency service facility location problem with considering disaster losses," 11th International Symposium on Operations Research and its Applications in Engineering, Technology and Management 2013 (ISORA 2013), Huangshan, 2013, pp. 1-6, doi: 10.1049/cp.2013.2249.
- [11] Deng X, Jiang Y, Yang LT, Lin M, Yi L, Wang M. Data fusion-based coverage optimization in heterogeneous sensor networks: A survey. *Information Fusion*. 2019 Dec 1;52:90-105.
- [12] Y. Singh, J. A. Lone, P. K. Singh, Z. Polkowski, S. Tanwar, and S. Tyagi, "Deployment and Coverage in Wireless Sensor Networks: A Perspective," 2019 11th International Conference on Electronics, Computers and Artificial Intelligence (ECAI), Pitesti, Romania, 2019, pp. 1-7, doi: 10.1109/ECAI46879.2019.9042091.
- [13] Muhammed T., Mehmood R., Albeshri A. (2018) Enabling Reliable and Resilient IoT Based Smart City Applications. In: Mehmood R., Bhaduri B., Katib I., Chlamtac I. (eds) *Smart Societies, Infrastructure, Technologies, and Applications*. SCITA 2017. Lecture Notes of the Institute for Computer Sciences, Social Informatics and Telecommunications Engineering, vol 224. Springer, Cham. https://doi.org/10.1007/978-3-319-94180-6_17.
- [14] Mohammed SulaimanBenSaleh, Raoudha Saida, Yessine Hadj Kacem, Mohamed Abid, "Wireless Sensor Network Design Methodologies: A Survey", *Journal of Sensors*, vol. 2020, Article ID 9592836, 13 pages, 2020. <https://doi.org/10.1155/2020/9592836>.
- [15] A. Yousaf, F. Ahmad, S. Hamid, and F. Khan, "Performance Comparison of Various LEACH Protocols in Wireless Sensor Networks," 2019 IEEE 15th International Colloquium on Signal Processing & Its

Applications (CSPA), Penang, Malaysia, 2019, pp. 108-113, doi: 10.1109/CSPA.2019.8695973 W. R. Heinzelman, A. Chandrakasan and H. Balakrishnan, "Energy- efficient communication protocol for wireless microsensor networks," Proceedings of the 33rd Annual Hawaii International Conference on System Sciences, Maui, HI, USA, 2000, pp. 10 pp. vol.2.

